

Revision date: 2020/09/11 Page: 1/15
Version: 2.0 (1010173/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

Ultrafuse® 17-4 PH

Recommended use of the chemical and restriction on use

Recommended use*: 3D Printing; for industrial use only

Details of the supplier of the safety data sheet

Company:

BASF CORPORATION 100 Park Avenue Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300

BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Substance number: 1010173 Chemical family: Polymer

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

^{*} The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.



Revision date: 2020/09/11 Page: 2/15 Version: 2.0 (1010173/SDS_GEN_US/EN)

Classification of the product

Skin Sens. 1 Skin sensitization Carc. 2 Carcinogenicity

Label elements

Pictogram:





Signal Word: Warning

Hazard Statement:

H317 May cause an allergic skin reaction. H351 Suspected of causing cancer.

Precautionary Statements (Prevention):

P280 Wear protective gloves, protective clothing and eye protection or face

protection.

P201 Obtain special instructions before use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P202 Do not handle until all safety precautions have been read and

understood.

P272 Contaminated work clothing should not be allowed out of the workplace.

Precautionary Statements (Response):

P308 + P313 IF exposed or concerned: Get medical attention.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P333 + P313 If skin irritation or rash occurs: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Precautionary Statements (Storage):

P405 Store locked up.



Revision date: 2020/09/11 Page: 3/15
Version: 2.0 (1010173/SDS_GEN_US/EN)

Precautionary Statements (Disposal):

P501 Dispose of contents/container in accordance with local regulations.

Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture. Upon mechanical treatment like e.g. cutting, grinding and/or polishing the product can release hazardous substances. Upon thermal and/or chemical treatment the product can release hazardous substances.

Labeling of special preparations (GHS):

This product is not combustible in the form in which it is shipped by the manufacturer, but may form a combustible dust through downstream activities (e.g. grinding, pulverizing) that reduce its particle size. UNDER HOT MELT PROCESSING CONDITIONS, WEAR PERSONAL PROTECTIVE EQUIPMENT TO PREVENT THERMAL BURNS.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Nickel

CAS Number: 7440-02-0 Content (W/W): >= 1.0 - < 5.0% Synonym: Nickel; Raney nickel

copper

CAS Number: 7440-50-8 Content (W/W): >= 1.0 - < 5.0% Synonym: No data available.

4. First-Aid Measures

Description of first aid measures



Revision date: 2020/09/11 Page: 4/15
Version: 2.0 (1010173/SDS_GEN_US/EN)

General advice:

Remove contaminated clothing.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. If symptoms persist, seek medical advice.

If on skin:

Wash thoroughly with soap and water Burns caused by molten material require hospital treatment. If irritation develops, seek medical attention.

If in eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

If swallowed:

Keep patient calm, remove to fresh air. Immediate medical attention required.

Most important symptoms and effects, both acute and delayed

Information on: copper

Symptoms: Overexposure may cause:, vomiting, abdominal cramps, metal fume fever, metallic taste in mouth, dyspnea, nausea, fever

Hazards: No hazard is expected under intended use and appropriate handling.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment:

Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media



Revision date: 2020/09/11 Page: 5/15
Version: 2.0 (1010173/SDS_GEN_US/EN)

Suitable extinguishing media: water spray, foam, dry powder

Special hazards arising from the substance or mixture

Hazards during fire-fighting:

Vapors/fumes may contain traces of combustible substances.

Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Dusty conditions may ignite explosively in the presence of an ignition source causing flash fire.

6. Accidental release measures

Further accidental release measures:

Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Avoid the formation and build-up of dust - danger of dust explosion. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition.

Personal precautions, protective equipment and emergency procedures

Wear suitable personal protective clothing and equipment. Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice.

Environmental precautions

Do not allow to enter soil, waterways or waste water channels.

Dispose of in compliance with the environmental protection requirements.

Methods and material for containment and cleaning up

For small amounts: Sweep/shovel up.

For large amounts: Sweep/shovel up. Vacuum up spilled product.

Reclaim for processing if possible. Ensure adequate ventilation. Avoid raising dust.



Revision date: 2020/09/11 Page: 6/15
Version: 2.0 (1010173/SDS_GEN_US/EN)

Nonsparking tools should be used. After decontamination, spill area can be washed with water.

7. Handling and Storage

Precautions for safe handling

Avoid inhalation of dusts/mists/vapours. Ensure adequate ventilation. Provide suitable exhaust ventilation at the drying process and in the area surrounding the melt outlet of processing machines. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Avoid the formation and deposition of dust.

Protection against fire and explosion:

Avoid dust formation. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids (2013 Edition) for safe handling.

Conditions for safe storage, including any incompatibilities

Segregate from oxidizing agents.

Suitable materials for containers: High density polyethylene (HDPE), Low density polyethylene (LDPE), Paper/Fibreboard

Further information on storage conditions: Avoid extreme heat. Avoid deposition of dust.

Storage stability:

Protect against moisture.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

Nickel

ACGIH TLV TWA value 1.5 mg/m3 Inhalable fraction;



Revision date: 2020/09/11 Page: 7/15 Version: 2.0 (1010173/SDS_GEN_US/EN)

copper

ACGIH TLV TWA value 0.2 mg/m3 fumes/smoke (copper (Cu)); TWA value 1 mg/m3 Dust and mist

(copper (Cu));

Advice on system design:

It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen deficient environment. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). Use only appropriately classified electrical equipment and powered industrial trucks.

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

Hand protection:

Wear gloves to prevent contact during mechanical processing and/or hot melt conditions.

Use additional heat protection gloves when handling hot molten masses (EN 407), e.g. of textile or leather.

Eve protection:

Safety glasses with side-shields. Wear splash goggles to protect from hot molten substance/product.

Body protection:

Standard work clothes and shoes.

General safety and hygiene measures:

Avoid inhalation of dust. Wear protective clothing to prevent contact during mechanical processing and/or hot melt conditions. Wash soiled clothing immediately.



Revision date: 2020/09/11 Page: 8/15
Version: 2.0 (1010173/SDS_GEN_US/EN)

9. Physical and Chemical Properties

Form: filament
Odour: odourless
Odour threshold: not applicable

Colour: grey

pH value: not applicable
Melting point: not determined
Boiling point: not applicable
Flash point: not applicable

Flammability: Not a flammable solid according to

UN transport regulations division 4.1

and GHS chapter 2.7.

Based on the structure or composition there is no indication of flammability

Lower explosion limit: For solids not relevant for

classification and labelling.

Upper explosion limit: For solids not relevant for

classification and labelling.

Autoignition: not applicable Vapour pressure: not applicable Density: (20 °C)

not determined not determined not applicable

not applicable

Partitioning coefficient noctanol/water (log Pow):

Self-ignition not self-igniting

temperature:

Bulk density:

Vapour density:

Thermal decomposition: > 300 °C

No decomposition if stored and handled as

prescribed/indicated. Thermal decomposition above the indicated temperature is possible. Prolonged thermal loading

can result in products of degradation being given off.

Viscosity, dynamic: not applicable

Viscosity, kinematic: not applicable, the product is a solid

Solubility in water: insoluble

Evaporation rate: The product is a non-volatile solid.



Revision date: 2020/09/11 Page: 9/15
Version: 2.0 (1010173/SDS_GEN_US/EN)

Other Information: If necessary, information on other physical and chemical

parameters is indicated in this section.

10. Stability and Reactivity

Reactivity

Corrosion to metals:

No corrosive effect on metal.

Oxidizing properties:

Not an oxidizer.

Reactions with water/air:

Reaction with: air

Flammable gases: no
Toxic gases: no
Corrosive gases: no
Smoke or fog: no
Peroxides: no

Reaction with: water
Flammable gases: no
Toxic gases: no
Corrosive gases: no
Smoke or fog: no
Peroxides: no

Formation of flammable gases:

Remarks: Forms no flammable gases in the

presence of water.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

The product is chemically stable.

No hazardous reactions if stored and handled as prescribed/indicated.



Revision date : 2020/09/11 Page: 10/15 Version: 2.0 (1010173/SDS_GEN_US/EN)

Conditions to avoid

Temperature: > 300 degrees Celsius

Prolonged exposure to elevated temperatures may result in exothermic decomposition accompanied by a pressure build-up in sealed containers. Avoid all sources of ignition: heat, sparks, open flame.

Incompatible materials

oxidizing agents

Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: monomers, gases/vapours, oxides, hydrocarbons, cyclic low molecular weight oligomers, Gaseous products of degradation can be given off if the product is greatly overheated.

Thermal decomposition:

> 300 °C

No decomposition if stored and handled as prescribed/indicated. Thermal decomposition above the indicated temperature is possible. Prolonged thermal loading can result in products of degradation being given off.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Inhalation of particulates may cause respiratory tract irritation. Ingestion may cause gastrointestinal disturbances. Contact with molten product may cause thermal burns. The resin in pelleted form poses a low hazard.

Oral

No applicable information available.



Revision date: 2020/09/11 Page: 11/15
Version: 2.0 (1010173/SDS_GEN_US/EN)

Inhalation

The inhalation of dusts represents a potential acute hazard.

Dermal

No applicable information available.

Assessment other acute effects

Based on available Data, the classification criteria are not met.

Irritation / corrosion

Assessment of irritating effects: May cause mechanical irritation.

<u>Skin</u>

May cause mechanical irritation.

Eye

May cause mechanical irritation.

Sensitization

Assessment of sensitization: The chemical structure does not suggest a sensitizing effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated exposure to the substance by dermal administration leads to effects similar to those found after single exposure. Repeated exposure to the substance by inhalative administration leads to effects similar to those found after single exposure. Repeated exposure to the substance by oral administration leads to effects similar to those found after single exposure. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Genetic toxicity



Revision date : 2020/09/11 Page: 12/15
Version: 2.0 (1010173/SDS_GEN_US/EN)

Assessment of mutagenicity: The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Carcinogenicity

Assessment of carcinogenicity: The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Reproductive toxicity

Assessment of reproduction toxicity: The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Teratogenicity

Assessment of teratogenicity: The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Other Information

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Persistence and degradability

Assessment biodegradation and elimination (H2O)



Revision date: 2020/09/11 Page: 13/15
Version: 2.0 (1010173/SDS_GEN_US/EN)

The product is not very soluble in water and can thus be removed from water mechanically in suitable effluent treatment plants.

Additional information

Add. remarks environm. fate & pathway:

The product has not been tested. The statements on environmental fate and pathway have been derived from the properties of the individual components.

Other ecotoxicological advice:

The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

13. Disposal considerations

Waste disposal of substance:

This product is not regulated by RCRA. This product is not regulated by CERCLA ('Superfund'). Incinerate in a licensed facility. Do not discharge substance/product into sewer system. Dispose of in accordance with national, state and local regulations.

Container disposal:

Dispose of in accordance with national, state and local regulations.

14. Transport Information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport IATA/ICAO



Revision date : 2020/09/11 Page: 14/15
Version: 2.0 (1010173/SDS_GEN_US/EN)

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

CERCLA RQ	CAS Number	Chemical name
100 LBS	7440-02-0	Nickel

State regulations

State RTK	CAS Number	Chemical name
NJ	7440-02-0	Nickel
	7440-50-8	copper
PA	7440-02-0	Nickel
	7440-50-8	copper
	50-00-0	Formaldehyde

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

WARNING: This product can expose you to chemicals including NICKEL, which is known to the State of California to cause cancer. For For more information, go to www.P65Warnings.ca.gov.

NFPA Hazard codes:

Health: 2 Fire: 1 Reactivity: 0 Special:

16. Other Information

SDS Prepared by:



Revision date : 2020/09/11 Page: 15/15 Version: 2.0 (1010173/SDS_GEN_US/EN)

BASF NA Product Regulations SDS Prepared on: 2020/09/11

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF DATA SHEET