


NF-A6x25 PWM

Noctua NF-A6x25 PWM Premium Fan



Featuring advanced aerodynamic design measures such as Flow Acceleration Channels and Noctua's AAO frame, the NF-A6x25 is a highly optimised, premium quality quiet fan in 60x25mm size. The PWM version sports Noctua's custom designed NE-FD1 IC for fully automatic speed control via 4-pin fan headers and comes with a Low-Noise-Adaptor to reduce the maximum speed during PWM control from 3000 to 2100rpm. Its superb running smoothness, SS02 bearing and Noctua's trusted premium quality make it an elite choice for the highest demands.

Reduced Motor Hub Size

Thanks to its streamlined, compact motor design, the NF-A6x25 PWM's motor hub is smaller than with conventional 6cm fans. This allows for more blade surface area and thus contributes to the NF-A6x25 PWM's superior airflow and pressure performance.

Flow Acceleration Channels

The NF-A6x25 PWM impeller features suction side Flow Acceleration Channels. By speeding up the airflow at the crucial outer blade regions, this measure reduces suction side flow separation and thus leads to better efficiency and lower vortex noise.

AAO Frame

Noctua's AAO (Advanced Acoustic Optimisation) frames feature integrated anti-vibration pads as well as Noctua's proprietary Stepped Inlet Design and Inner Surface Microstructures, both of which further refine the fan's performance/noise efficiency.

Stepped Inlet Design

Noctua's Stepped Inlet Design adds turbulence to the influx in order to facilitate the transition from laminar flow to turbulent flow, which reduces tonal intake noise, improves flow attachment and increases suction capacity, especially in space restricted environments.

Inner Surface Microstructures

With the tips of the fan blades ploughing through the boundary layer created by the Inner Surface Microstructures, flow separation from the suction side of the blades is significantly suppressed, which results in reduced blade passing noise and improved airflow and pressure efficiency.

Low-Noise Adaptor

The NF-A6x25 PWM is supplied with a Low-Noise Adaptor (L.N.A.) that reduces the maximum fan speed from 3000 to 2100rpm. The L.N.A. can be used either to run the fan at a fixed speed of 2100rpm or to cap the maximum speed when using automatic PWM control.

Custom designed PWM IC with SCD

Supporting fully automatic PWM speed control, the NF-A6x25 PWM uses Noctua's novel, custom designed NE-FD1 PWM IC that integrates Smooth Commutation Drive (SCD) technology. By providing smoother torque impulses, SCD suppresses PWM switching noises and thus makes the fan quieter at low speeds.

SS02 Bearing


The NF-A6x25 PWM features the further optimised second generation of Noctua's renowned, time-tested SSO bearing. With SS02, the rear magnet is placed closer to the axis to provide even better stabilisation, precision and durability.

Extensive cabling options

The fan's short 20cm primary cable minimises cable clutter in typical applications while the supplied 30cm extension provides extended reach when necessary. Both cables are fully sleeved and a 4-pin Y-cable allows to connect a second fan to the same PWM fan header for automatic control.

6 years manufacturer's warranty

Noctua fans are renowned for their impeccable quality and outstanding longevity. Like all Noctua fans, the NF-A6x25 PWM features an MTBF rating of more than 150.000 hours and comes with a full 6 years manufacturer's warranty.



SPECIFICATIONS

Size	60 x 60 x 25 mm	
Bearing	SS02	
Blade Geometry	A-Series with Flow Acceleration Channel	
Max. Input Power/Operating Voltage	0.96 W/12V	
MTBF	> 150.000 h	

NF-A6x25 PWM	w/o adaptor	with L.N.A.
Max. Rotational Speed (+/-10%)	3000 RPM	2100 RPM
Max. Airflow	29.2 m³/h	20.9 m³/h
Max. Acoustical Noise	19.3 dB(A)	12.1 dB(A)
Max. Static Pressure	2.18 mmH2O	1.08 mmH2O

LOGISTICAL DATAS

Product Labeling
Noctua NF-A6x25 PWM

EAN-No.
471612331563-6

UPC-No.
84243101252-4

Dimensions (HxWxD)
60 x 60 x 25 mm

Weight
195 gr

Warranty
6 Years

MSPR
14.90 EUR

Packaging Unit
36 Pcs.

Dimensions / Unit (HxWxD)
395 x 385 x 380 mm

Weight / Unit
8.9 kg

SCOPE OF DELIVERY

NF-A6x25 PWM Premium Fan
Low-Noise Adaptor (L.N.A.)
4-Pin Y-Cable
30cm Extension Cable
4x Anti-Vibration Mounts
4x Fan Screws